


FABORY-RIVEKLE - BLIND RIVET NUTS WITH COUNTERSUNK HEAD - STEEL ZINC PLATED, YELLOW PASSIVATED

FABORY-RIVEKLE - BLINDKLINKMOEREN MET VERZONKEN KOP - STAAL ELVZ, GEEL GEPASSIVEERD

FABORY-RIVEKLE - ECROUS NOYES AVEC TETE FRAISEE - ACIER ELECTRO-ZINGUE, PASSIVE JAUNE


FABORY-RIVEKLE - REMACHES ROSCADOS CON CABEZA FRESADA - ACERO GALV. ELECTR. PASIVADO AMARILLO

FABORY-RIVEKLE - BLINDNIETMUTTERN MIT SENKKOPF - STAHL VERZINKT, GELB PASSIVIERT


 ISO : -
 DIN : -
 NEN : -
 ANSI : -
 BS : -
 NF : -

CODE

YELL. PS.

69180

 Ordering example:
69180 3FB30
M
St

Type	3FB30	4FB30	4FB50	5FB40	5FB65	6FB40	6FB65	6FB90	8FB40	8FB65	10FB40
d ①	M3	M4	M4	M5	M5	M6	M6	M6	M8	M8	M10
Grip range	1,3-3	2-3	3-5	1,5-4	4-6,5	1,5-4	4-6,5	6,5-9	1,5-4	4-6,5	1,5-4
D	5	6	6	7	7	9	9	9	11	11	13
B	7,2	8,2	8,2	9,6	9,6	11,7	11,7	11,7	13,5	13,5	15,5
E	1,4	1,4	1,4	1,6	1,6	1,6	1,6	1,6	1,6	1,6	1,6
s ②	2,5-1,3	3,8-1,7	3,8-1,7	5,5-2,5	5,5-2,5	4,7-2,2	4,7-2,2	4,7-2,2	5,5-3	5,5-3	5,8-3,3
L2	13	15,5	17	20	23	23	26	29	26	29	32

articlenumber

Type	YELL. PS. 69180 F07	☒	Type	YELL. PS. 69180 F07	☒	Type	YELL. PS. 69180 F07	☒
3FB30	030.030	500	5FB65	050.065	500	8FB40	080.040	250
4FB30	040.030	500	6FB40	060.040	500	8FB65	080.065	250
4FB50	040.050	500	6FB65	060.065	500	10FB40	100.040	250
5FB40	050.040	500	6FB90	060.090	250			

 ① Blind rivet nuts M3 are **not** chamfered.

 ② s = shortening **after** riveting.
 Hole diameter = D + 0,1 mm.