Pos.-no.	Piece	Part name			Material
381	2	Feather key	D22x14x100	DIN 6885	Steel
377	3	Spring dowel sleeve	16x50	ISO 8752	Steel
376	1	Bearing	Ø110xØ105x60		Steel-PTFE
375	1	Retaining ring	120x4	DIN 472	Steel
373.02	2	Socket head screw	M6x16	DIN 7984	Steel
373.01	10	Socket head screw	M16x40	DIN 912	Steel
371.06	1	O-ring	11-2		FPM
371.05	1	O-ring	108-3		FPM
371.04	1	O-ring	113-3		FPM
371.03	1	O-ring	100-3		FPM
371.02	1	O-ring	85-3		FPM
371.01	2	O-ring	85-3		FPM
335.02	4	Lifting lug			Steel
333	1	Bleeder plug	1/2 NPT		Stainless steel
327.02	1	Bearing	Ø90xØ85x17.5		Steel-PTFE
327.01	1	Bearing	Ø105xØ100x45		Steel-PTFE
323.04	1	Bearing			Bronze
323.03	1	Seal ring	Ø90xØ85x9.5		PTFE
323.02	1	Packing ring	Ø119.8xØ85x5.1		GRAPHITE
323.01	1	Bearing	Ø104.5xØ85x2.5		Steel-PTFE
320	1	Trunnion			Steel C 22.8 / P250GH
318	1	Flange (peg)			Steel St 52-3 / S355J2+N
313.02	1	Gland			Steel C 22.8 / P250GH ⊕
313.01	1	Stem bearing			Steel St 52-3 / S355J2+N
312	1	Stem			Stainless steel 1.4006 V (AISI 410)
311	40	Spring			Stainless steel
307.03	2	O-ring	Body seat ring (double-piston) EDP-no. 307.9414		FPM
307.02	2	Delta-ring			FPM
307.01	2	Support ring			Steel
306	1	Ball			ASTM A350/LF2, ENP
305	2	Body closure			Steel TStE 355 / P355NL1 ⊕
304	2	Flange			Steel ASTM ~~A105~~ A350 LF2 ⊕
301	1	Body			Steel TStE 355 / P355NL1 ⊕

N°	REVISION	DATE	NAME
2	was -10°C up to +100°C	25.6.07	Ko
1	was Rz63, BR 400	22.3.06	Ko

	DATE	NAME
2003		
DRAWN	01.07.	Kottsieper
CHECKED		
NORM		

MATERIAL
Siemens-construction
Page 3 of 3

SCALE
%

DIMENSIONS WITHOUT TOLERANCES ACC.TO:
DIN ISO 2768 T.1-M
DIN ISO 2768 T.2-K
DIN 1683

Ball valve BBF/FSA
DN300 Class600-RF
EG-type-tested
with test connection 1/2 NPT
and worm gear

ALL RIGHTS IN THIS DRAWING RESERVED,
ALSO IN CASE OF PATENT OR DESIGN REGISTRATION

REPLACEMENT FOR:
REPLACED BY:

BÖHMER

DRAWING-N°:
9.085.300.040.00.02

DOCU-N°:
0856019-02-GB-03-2D

EDP-N°:
085.35300100.6019

Nur zur Information