

Type	Length x Width x Height [mm]	Stroke [mm]	Duty cycle [%]	Initial force [N]	Apparent power Stroke starting [kVA]	End power [N]	Apparent power Stroke end [kVA]	Response time [ms]
WL125	65 x 60 x 85	15	100	13	0.400	51	0.048	95
WL125	65 x 60 x 85	15	40	18	0.570	81	0.110	95
WL125	65 x 60 x 85	15	25	21	0.670	101	0.150	95
WL125	65 x 60 x 85	15	15	26	0.770	121	0.220	95
WL125	65 x 60 x 85	15	5	36	1.000	141	0.400	95
WL230	77 x 70 x 94	20	100	27	1.000	102	0.070	95
WL230	77 x 70 x 94	20	40	40	1.350	122	0.190	95
WL230	77 x 70 x 94	20	25	47	1.600	152	0.280	95
WL230	77 x 70 x 94	20	15	57	2.000	182	0.450	95
WL230	77 x 70 x 94	20	5	72	2.500	202	0.925	95
WL330	87 x 76 x 113	25	100	55	1.700	133	0.100	95
WL330	87 x 76 x 113	25	40	77	2.100	153	0.187	95
WL330	87 x 76 x 113	25	25	100	2.420	183	0.385	95
WL330	87 x 76 x 113	25	15	125	3.300	213	0.660	95
WL330	87 x 76 x 113	25	5	155	4.620	253	1.200	95
WL430	107 x 93 x 144	30	100	76	2.100	166	0.110	95
WL430	107 x 93 x 144	30	40	99	3.565	260	0.340	95
WL430	107 x 93 x 144	30	25	126	4.620	300	0.685	95
WL430	107 x 93 x 144	30	15	164	5.500	380	1.190	95
WL430	107 x 93 x 144	30	5	200	7.040	430	2.400	95
WL450	108 x 108 x 158	40	100	105	3.600	210	0.100	95
WL450	108 x 108 x 158	40	40	155	6.160	330	0.280	95
WL450	108 x 108 x 158	40	25	220	8.800	410	0.500	95
WL450	108 x 108 x 158	40	15	275	10.120	460	0.880	95
WL450	108 x 108 x 158	40	5	335	12.980	500	1.826	95
WL540	142 x 99 x 186	40	100	120	4.625	253	0.121	95
WL540	142 x 99 x 186	40	40	205	9.240	383	0.462	95
WL540	142 x 99 x 186	40	25	254	9.570	430	0.638	95
WL540	142 x 99 x 186	40	15	295	11.660	464	1.232	95
WL540	142 x 99 x 186	40	5	390	14.300	513	2.244	95