

Three-Phase-Asynchronous-Motor ACM 200 LB 6/PHE

IE3AC20LB600

General data

Kind of motor	3~
Type designation	ACM
Frame size	200
Mounting form	B3
Frame execution	L
Frame material	Cast iron
Insulation class	F/B
Terminal box location	top DE
Terminal box orientation	0° cable gland right side
Weight (kg)	251,00
Rotation Direction	right /left
Vibration level	A
Balancing method	half key
cooling type	IC411
Executed acc. to	IEC 60034-1
noise level	IEC 60034-9

Electrical data

Power 1 50Hz (kW)	22,00
Power 1 60Hz (kW)	26,40
Frequency (Hz)	50/60
Voltage 50Hz (V)	400/690
Voltage 60Hz (V)	460/795
Voltage/Frequency tolerance (not valid for range voltage)	range B
Connection	Δ/Y
Poles	6
Efficiency 100% 50Hz (%)	92,2
Efficiency 75% 50Hz (%)	92,2
Efficiency 50% 50Hz (%)	90,4
Efficiency 100% 60Hz (%)	94,1
Efficiency 75% 60Hz (%)	92,2
Efficiency 50% 60Hz (%)	90,4
Power factor	0,81
Starting current (Ia/In)	7,3
Starting torque (Ma/Mn)	2,1
Breakdown torque (Mk/Mn)	2,1
Current 50Hz (A)	42,52/24,65
Current 60Hz (A)	43,47/25,15
Eff.Cl.50Hz	IE3
Eff.Cl.60Hz	IE3

Motor characteristics

Color	RAL7030
Paint surface	shiny
Protection class	IP55
Cable gland size (cable connection)	2xM50x1,5
Cable gland size (option)	M20x1,5
Cable gland type	Standard
Shaft end (mm)	55 x 110
Shaft material	C45
Specification NDE	Plastic fan

Mechanical data

Torque (Nm)	214,39/214,39
Rotation speed (1/min)	980/1176
Bearing DE	6312.ZZ.C3
Bearing NDE	6312.ZZ.C3
Mounting of bearing DE	loose bearing
Mounting of bearing NDE	fixed bearing
Bearing lifetime (h)	20000
Moment of inertia (kgm²)	0,36

Influencing factors


Duty	S1
Ambient temperature (°C)	-20 up to +40
Height of location (m)	1000

Additional options

Protection winding	PTC 150°C
--------------------	-----------

Drawings

Three-Phase-Asynchronous-Motor ACM 200 LB 6/PHE
IE3AC20LB600



LM	IPE/KK	DH	K	ED	G	LL	L	AG	GD	EB	F	HA	H	E	D	C	BB	B	AD	AC	AB	AA	A
812	M50x1,5	M20x42	18,5	5,00	49,00	190,00	757,00	210,00	10	100	16	25	200	110	55	133	369	305	299	397	388	70	318